



SECTION 1: DESCRIPTION & BENEFITS

- 10mm low-density closed-cell EPE foam as carrier
- Coated with special formula of very high tack adhesive
- Laminated with yellow paper easy release liner
- Hard to deform, breakage proof
- Outstanding shake proof, acoustic insulation
- Good elasticity, easy recovery of shape
- Great air sealing, moisture sealing
- Outstanding conformity to uneven surfaces



SECTION 2: SPECIFICATIONS

Product Characteristics	Performance Data	Test Method
Carrier Color	White	Visual
Liner Color	White	Visual
Density	≥ 25 KG/m ³	ASTM D-3575
Peel Adhesion	≥ 6 N/CM	ASTM D-3330
Loop Tack	16 # steel ball	GB/T 4852-84
Tensile strength	16 N/CM	ASTM D3759
Elongation	≥ 180%	ASTM D-3330
Temp Resistance	-30°C~80°C	

SECTION 3: APPLICATIONS & OTHER DETAILS

- Packaging cushion material
- Automotive decoration
- Furniture inner decoration
- Anti-static padding material for electronic device

Sliced roll width available (or customized): 10-1600mm

Standard Length: 100-2000mm

Tolerance: Thickness: +/- 10% Width: +/-1.0mm Length: +/- 0.4mm

Storage: Indoor storage: -5°C-40°C (humidity: < 80%), cool & dry, free of direct sunlight

Shelf Life: 12 months in room temp.



N.B. Please keep the operating surface clean, dry, and free of grease or other dirt & dust. So that **Egret Tape** can have a best performance.

Changzhou Egret Manufacturing Co., Ltd

No.4, Tongshun Rd, Henglin Town, Changzhou 213101 • China

T: +86 519 8878 9969 Ext. 807 Email: info@egretmfg.com Website: www.egretmfg.com