



SECTION 1: DESCRIPTION & BENEFITS


- Blue thin polyethylene film with good tensile strength
- With silicone coating on PE non-adhesive side for easy release
- Easy hand-tear or tear-resistance is available according to customer
- Flexible PE material enables to stretch and conform to irregular surfaces
- PE film color can be white or blue, transparent
- Coated with high performance acrylic adhesive
- Excellent weather ability
- Good UV resistance for up to 6 months
- Good aging resistance for both indoor & outdoor use

SECTION 2: SPECIFICATIONS

PE Film Thickness	25 micron (1.0 mil)
Adhesive Thickness	5 micron (0.2 mil)
Total Thickness	30 micron (1.2 mil)
Adhesion Strength	120 g/25mm
Static Shear	> 24 Hrs
Tensile Strength	2.03 kgf/25mm
Elongation at Break	≥ 180.0%
Service Temp.	-20 ~ + 80°C (-4 ~ +176 °F)
Operating Temp.	0 ~ +40°C (+32 ~ +104 °F)

SECTION 3: APPLICATIONS & OTHER DETAILS

- Duct board closure
- Tape closure
- Metal, glass surface protection
- General purpose like: protecting, sealing, masking, insulation, packaging, etc.



Sliced roll width available (or customized): 50,60, 600, 900 mm, etc.

Roll length: 50m, 100m

Tolerance: Thickness: +/- 0.0015mm Width: +/-1.0mm Length: +/- 0.4m

Storage: Indoor storage: -5°C-40°C(humidity: < 80%), cool & dry, free of direct sunlight

Shelf Life: 12 months in room temp.

N.B. Please keep the operating surface clean, dry, and free of grease or other dirt & dust. So that **Egret Tape** can have a best performance.

Changzhou Egret Manufacturing Co., Ltd

No.4, Tongshun Rd, Henglin Town, Changzhou 213101 • China

T: +86 519 8878 9969 Ext. 807 Email: info@egretmfg.com Website: www.egretmfg.com